


## Rainshower System

### 7765-BF-80P1

#### INTRODUCTION:

The simple tube-form design, brings out the modern beauty of linear shape. This series combines the refined surface, multiple functions, and humanization operating design as a perfect elegant demonstration of modern bath equipment. In the meanwhile, it inherits the durability and the convenient from the previous product generation, making a comfortable bathing space for customers.



unit:mm

#### DESCRIPTION:

- 1.Brass of casting body meets ISO CuZn40Pb standard.
- 2.Finish meets the standard of ASTM-SC2.
- 3.The faucet should be used at the water pressure from 1.5 to 4.5 kg/cm<sup>2</sup>.
- 4.Adjust the water supply to hand shower or rain shower by pressing diverter.
- 5.Ceramic valve with CERAMTEC ceramic disc/(Germany).
- 6.Elastic shower hose can be extended from 1.5 meter to 2 meter.
- 7.Adjustable angle of the hand-shower bracket.
- 8.The available distance between two centers of wall water-outlet is 122mm to 178mm.
- 9.The swiveling shower arm could be adjusted for the different spray position within available range.
- 10.Coordinates with other products in Pan I collection.

#### Certification:

#### Fixing Kits:

- 1.SUS 304 Stainless Steel Screws\*2.
- Hex Key 1/8"\*1.
- Set Screw\*2.
- Plastic Anchors\*2.

#### AWARD: